

Arcylic Fiber Packing
CAZ- 230P,230R 230G

Compression Packing

CONSTRUCTION:



CAZ 230P Arcylic Fiber Packing with PTFE

Braided from high strength arcylic synthetic fiber pre-impregnated with PTFE, and re-impregnated during square braiding. It has excellent properties of sealing, lubricating and resistance to chemicals. **230L** is arcylic fiber packing with oil and few PTFE



CAZ 230R Arcylic Fiber Packing with Rubber Core

High elastic red silicone rubber core can absorb vibration, to control leakage, suitable for worn-out pumps.

CAZ 230G Arcylic Fiber Packing Treated with Graphite

Braided of high strength Arcylic synthetic fiber, treated with graphite and special lubrication. Much of graphite filler increases the service temperature and the density of the packing.

APPLICATION:

230 230L 230R	Excellent multi-service for a wide variety of uses throughout a plant. Used in pumps and valves, and can handle most chemicals except strong acid, strong alkali and strong oxidizer. Especially for the condition of middle temp. high-pressure, high-speed, and where contamination is not permitted.
230G	Universal packing for pumps and valves, and handle water, air, steam, mild acids and alkalis, all kinds of organic solvents and Chemicals. Especially suitable for the condition of high-temperature, high-pressure, medium speed.

PARAMETER:

	230, 230L	230G
T	260°C	350°C
PH	1~13	1~13
V	20m/s	15m/s
Rotating	20bar	25bar
Reciprocating	80bar	100bar
Valve	100bar	150bar
D(g/cm ³)	1.1~1.3	1.1~1.3



PACKAGING:

in coils of 5 or 10 kg, other package on request.
as prepressed rings----**R230, R230R, R230G**
as precut length



DIMENSIONS:

Size mm	5	6	8	10	12	13	14	15	16	18	20	22	25
appr. m/kg	33	23	13	8.0	5.5	5.0	4.2	3.7	3.2	2.5	2.1	1.7	1.3
Appr. ft/lb	49	34	19	12	8.2	7.4	6.2	5.5	4.8	3.7	3.1	2.5	1.9
kg/coil	5 or 10												