

Elastop™ Material
CAZ 460 Series Rubber

Joint Sheets

NBR、SBR、CR、EPDM...

CAZ **Elastop™** Rubber sheets are manufactured for your different requirements such as oil-resisting, acid and alkali-resisting, cold and heat-resisting, insulation, anti-seismic etc. They can cut into various gaskets, used in chemicals, elections, fire-resisting and food. They also can be used as sealer, buffer rubber ring, rubber mat, sealing strip and for the decoration of flights of step and ground of hotel, port boats and ships, vehicles etc.



| Style | Products | Color | g/cm ³ | Hardness sh | Elongation % | Tensile strength | Temp °C |
|----------|--------------------------------------|-----------|-------------------|-------------|--------------|------------------|----------|
| 460BR | Black rubber sheet | Black | 1.6 | 70±5 | 250 | 3.0Mpa | -5~+50 |
| 460RC | Black rubber sheet with cloth insert | Black | 1.6 | 70±5 | 220 | 4.0Mpa | -5~+50 |
| 460NBR | Nitrile rubber sheet | Black | 1.5 | 65±5 | 280 | 5.0Mpa | -10~+90 |
| 460SBR | Styrene-butadiene rubber sheet | Black/red | 1.5 | 65±5 | 300 | 4.5Mpa | -10~+90 |
| 460CR | Neoprene rubber sheet | Black | 1.5 | 60±5 | 300 | 4.5Mpa | -10~+90 |
| 460EPDM | Ethylene propylenediene rubber sheet | Black | 1.4 | 65±5 | 300 | 8.0Mpa | -20~+120 |
| 460SC | Silicone rubber sheet | White | 1.2 | 50±5 | 400 | 8.0Mpa | -30~+180 |
| 460VITON | Fluorine rubber sheet | Black | 2.0 | 70±5 | 350 | 8.0Mpa | -50~+250 |
| 460RO | Oil-resisting rubber sheet | Black | 1.5 | 65±5 | 280 | 5.0Mpa | -10~+60 |
| 460RCH | Cold & heat-resisting rubber sheet | Black | 1.6 | 65±5 | 280 | 4.5Mpa | -20~+120 |
| 460RAA | Acid & alkali-resisting rubber sheet | Black | 1.6 | 65±5 | 280 | 4.5Mpa | -10~+80 |
| 460RI | Insulating rubber sheet | Black | 1.5 | 65±5 | 300 | 5.0Mpa | -10~+80 |
| 460RFI | Fire-resistance rubber sheet | Black | 1.7 | 65±5 | 280 | 4.5Mpa | -5~+60 |
| 460FR | Food grade rubber sheet | Red/white | 1.6 | 60±5 | 300 | 6.0Mpa | -5~+50 |

Width: 1000mm, 1200mm, 1500mm, 2000mm, Length on request,
Normal: 50kg/roll, **Thickness:** 1~60mm;

Each rubber sheet can be reinforced with fabric cloth, thickness≥1.5mm;
More other rubber products are available on request.