

*Asbestos Beater Sheet*  
**CAZ-ASB 400, 400V**

*Joint Sheets*

**CONSTRUCTION:**

**CAZ 400 Asbestos emulsion sheet**

It is made from synthetic emulsion, asbestos fiber and filling material. Normal used for automobile, agricultural machinery, motorcycle, engineering machinery etc., suitable for lubricating oil under temperature 200°C

**CAZ 400V Vulcanized Asbestos beat sheet**

It has smooth face and high density compared with Style 400

**APPLICATION & PARAMETER:**

Gasket materials for explosion engine cylinder gaskets and chemical gaskets  
Suitable to sealing lubricating oil at highest temperature 200°C  
400 Asb strip is normal for filler of spiral wound gasket.

Item		Style	
		400	400V
Density	g/cm <sup>3</sup>	0.9~1.1	1.2~1.4
Tensile strength	≥Mpa	2.5	5
Compressibility	≥%	40±7	20±5
Recovery	≥%	20	40
Stress relaxation	≤%	30	30
In 20# aviation oil, 150°C, 30min	Oil absorption	≤50%	≤30%
	Thick. increase	≤6%	≤12%
In water 15~30°C, 5h	Thick. increase	≤6%	≤12%

Normal color: Grey, Black, White, other color on request

Also available with anti-stick : **400S, 400VS**  
or graphite coating : **400G, 400VG**

**TOLERANCE:**

Item	Tolerance	In same sheet
Thickness	±mm	mm
0.5	0.05	0.06
0.6-0.8	0.06	0.08
1-2	0.08	0.08

**DIMENSIONS:**

**Sheets:**

Width: 500mm; 1000mm  
Length: 500mm; 1000mm; 1200; 1500mm  
Thickness: 0.3~2.0mm

**Cut gaskets:**

G400, G400V

Dimension according to drawings or specifications and standards.

