

Asbestos Rubber Sheet
CAZ-CAF 412,413,414

Joint Sheets

CONSTRUCTION:

CAZ CAF are made from selected asbestos fibre, natural rubber, filling material and dye. A price worthy quality of dependable performance, plus adaptability to many sealing requirements makes this jointing the most economical sheet packing choice in the wide range of industrial fields.

PARAMETER:

Item	Style			
	412	413	414	414-2
Tensile strength≥Mpa	9	12	15	19
Aging coefficient	0.9	0.9	0.9	0.9
Loss on ignition ≤%	30	30	28	28
Compressibility ≥%	12±5	12±5	12±5	12±5
Recovery ≥%	40	40	45	45
Density g/cm ³	1.6~2.0			
Tmax: °C	200	300	400	450
Pmax: Mpa	2.3	3.5	5.0	6.0
Resistance to media	Water, seawater, steam, diluted acid & alkali, gases, alcohols, salt solutions etc. under temperature and pressure.			

Lower Grade on request
 Available color: Purple, red, black, grey etc.
 Available with tin steel, copper, SS304 etc. wire mesh insertion (**41*M**)
 Also available with anti-stick (**41*S**) or graphite coating (**41*G**)
 With your logo on request

DIMENSION:

Sheets:

4000×1500mm; 2000×1500mm; 1500×1500mm;
 1500×1000mm; 1270×1270mm; 3810×1270mm;
 3810×2700mm
 Thickness: 0.5~6mm

Cut gaskets

G412~G414

Dimension according to drawings or and standards



All data quoted are based on our extensive tests and years of experience, however, they can only serve as guide values. Failure to select proper sealing products could result in property damage and/or serious injury. Specifications are subject to change without notice.