

Supper P&T Asbestos Rubber Sheet
CAZ-CAF 415,415G,415MG

Joint Sheets

CONSTRUCTION:

CAZ CAF415 is made from selected asbestos fiber, natural rubber, filling material and dye. A price worthy quality of dependable performance, plus adaptability to many sealing requirements makes this jointing the most economical sheet packing choice in the wide range of industrial fields.

CAZ 415G is CAF 3050 with both graphite coating

CAZ 415MG is CAF 3050 reinforced by wire mesh with both graphite coating

PARAMETER:

Item	Style		
	415	415G	415MG
Tensile strength≥Mpa	19	19	25
Aging coefficient	0.9	0.9	0.9
Loss on ignition ≤%	28	28	28
Compressibility ≥%	12±5	12±5	12±5
Recovery ≥%	45	45	45
Density g/cm ³	1.8~2.0	1.8~2.0	2.0~2.2
Tmax: °C	500	550	550
Pmax: Mpa	12.0	12.0	20
Normal color	Purple red	Graphite	Graphite
Resistance to media	Water, seawater, steam, diluted acid & alkali, gases, alcohols, salt solutions etc. under temperature and pressure.		

Also available with anti-stick: **415S, 415GS, 415MGS**

DIMENSION:

Sheets: Thickness: 0.4~6mm
2000×1500mm; 1500×4000mm;
1500×1500mm; 1500×1000mm;
1270×1270mm; 3810×1270mm

New: 3810×2700mm

Cut gaskets:

CAF G415, G415G, G415MG

Dimension according to drawings or specifications and standards

