

Ramie / Flax Fiber Packing
CAZ- 220P, 220R, 220G, 222V

Compression Packing

CONSTRUCTION:



CAZ 220P Ramie Fiber Packing with PTFE

Highest quality ramie fiber impregnated with light-colored, special PTFE and inert lubricant during square plaiting operation. It can prevent product contaminated. Low maintenance, easy-to-control, it is not harsh on shafts and stems. Material Flax is also available on request.



CAZ 220R Ramie packing with silicon Rubber Core

High elastic silicon core can absorb vibration, to control leakage.

CAZ 220G Ramie Packing with graphite & oil impregnation

Square braided construction, graphite coated and mineral oil lubricated throughout.

CAZ 222V Flax Packing with Grease

Square braided construction, vaseline coated and special grease lubricated throughout.

APPLICATION:

220P 220R 222V	For pumps, refiners, filters and valves in the brewing and beverage industry, shipbuilding and other fields. Especially resistant to abrasive media in the paper industry.
220G	A medium hard packing which is lubricated and graphited throughout. Extremely low frictional characteristics where minimum shaft wear is essential. Rot resistant and ideal for marine use, handling cold water, brine and cold oils.

PARAMETER:

Style	220(R),222V	2400G
Density	1.25g/cm ³	1.25g/cm ³
PH range	5~11	6~8
Maximum Temperature °C	130	100
Pressure bar	Rotating	20
	Reciprocating	20
	Static	30
Shaft speed	m/s	10
		6



PACKAGING:

in coils of 5 or 10 kg, other package on request.
as packing rings----**R220P,R220R, R220G,R222V**
as precut length

DIMENSIONS:

Size mm	5	6	8	10	12	13	14	15	16	18	20	22	25
appr. m/kg	33	23	13	8.0	5.5	5.0	4.2	3.7	3.2	2.5	2.1	1.7	1.3
Appr. ft/lb	49	34	19	12	8.2	7.4	6.2	5.5	4.8	3.7	3.1	2.5	1.9
kg/coil	5 or 10												