

NA Beater Sheet
CAZ-NAB 420, 420V

Joint Sheets

CONSTRUCTION:

CAZ NAB 420 Non-asbestos beater sheet is made from synthetic emulsion, plants fiber and filling material. The production is used for position of lubrication system, which has the property of good compressibility and coefficient of resilience, in addition, the inside of gasket can properly swell to meet oil, that make up of the shortcoming that procession machining precision is not enough, which affected self-sealing.

Style 420V is Vulcanized non-asbestos beater sheet with smooth faces.

PARAMETER:

Used in Automobile, farm machinery, motors, engineering etc. It can be used in oil system and water supply system at temperature 150°C

Item	Unit	420	420V
Density	g/cm	0.9~1.1	1.2~1.4
Tensile strength	≥Mpa	12.7	
Compressibility	%	15±5	
Recovery	≥%	45	
Stress relaxation	≤%	35	
Weight increase (in oil)	≤%	35	
Thickness increase (in oil)	≤%	15	

Normal color: Grey, Black, other color on request

Also available with anti-stick : **420S, 420VS**
or graphite coating: **420G, 420VG**

TOLERANCE:

Item	Tolerance	In same sheet
Thickness	±mm	mm
0.5	0.05	0.06
0.6-0.8	0.06	0.08
1-2	0.08	0.08

DIMENSIONS:

Sheets:

Width: 500mm; 1000mm
Length: 500mm; 1000mm; 1200; 1500mm
Thickness: 0.3~2.0mm

Cut gaskets:

G420, G420V

Dimensions according to drawings or specifications and standards.

