

Reinforced (Non-)Asbestos Beater Sheet
CAZ-420T, 400T

Joint Sheets

CONSTRUCTION:

CAZ 420T is made of 420 Non-asbestos gasket sheet reinforced with tanged 0.2-0.25mm Carbon Steel. It is extensively applied in manufacturing various motor gaskets. It is a new material that will substitute asbestos products. The product has excellent performance in dilatibility, sealing equality and long life etc., Mainly applied in automobile farming machine, motorcycle and engineering etc., it is also can be used in high strength gaskets and cylinder gaskets etc.

CAZ 400T is made of 400 asbestos emulsion sheet reinforced with tanged 0.2-0.25mm Carbon Steel

PARAMETER:

Item	Style
	420T, 400T
Density g/cm ³	1.30~1.50
Tensile strength ≥Mpa	12.7
Compressibility ≥%	10±5
Recovery ≥%	40
Sealing performance	<0.5cm ³ /min
Performance of heat-resistance	150-300°C

Normal colour: Black, Gray, Graphite etc.
Available with SS304. wire mesh insertion
Also available with anti-stick silicon resin---**420TS, 400TS**
or graphite coating---**420TG, 400TG**

DIMENSIONS:

Sheets:

500×1000mm; 500×1200mm; 500×1500mm;
510×1016mm; 510×1530mm;
1000×1000mm; 1000×1500mm;
Thickness: 1.0~2.4mm

Packing:

in strong export standard cases of about 1000 kgs net each

Cut gaskets:

G420T, G400T

Dimensions according to drawings or specifications and standards.

