

Other Process Lines

Sealing Machines

Style	Specification	Application
	<ol style="list-style-type: none"> 1. Power:380AV, 50HZ, 5 KW; 2. Working space: 4×6m; 3. Max. Output: 500kg/day 	<p>For making expanded graphite ("worm")</p> <p>Raw materials: Acid graphite-5099 Heated by LPG or oil</p>
880 GEL--Graphite Expanding Line		
	<ol style="list-style-type: none"> 1. Power:380AV, 50HZ, 15 KW; 2. Working space: 4×15m; 3. Max. Output: 300kg/day 	<p>Composite machine +Cutter</p> <p>For making expanded graphite yarn, normal size: 2g/m, 3g/m, 5g/m The reinforced material can be cotton, glassfiber etc</p>
880 GYL--Graphite Yarn Process Line		
	<ol style="list-style-type: none"> 1. Power:380AV, 50HZ, 30 KW; 2. Working space: 10×20m; 3. Max. Output: 1000kg/day 	<p>For making expanded graphite roll With width 1000mm and thickness 0.2~1.2mm</p>
880 GRL-- Graphite Roll Process Line		
	<ol style="list-style-type: none"> 4. Power:380AV, 50HZ, 30 KW; 5. Working space: 10×12m; 6. Max. Output: 500kg/day 	<p>From dry asbestos fiber to wet asbestos yarn (Dust free) 2g/m, 3g/m, 5g/m etc.</p>
880 AYL--Asbestos Yarn (Dust Free) Process Line		
	<ol style="list-style-type: none"> 1. Power:380AV, 50HZ, 30 KW; 2. Working space: 20×30m; 3. Max. Output: 1000kg/day 4. Thickness: 0.4~6.0mm 	<p>For making asbestos-rubber sheet, oil-resisting asbestos-rubber sheet, and non asbestos sheet.</p> <p>Max. size: 4000×1500mm 4500×1500mm 3810×1270mm</p>
880 ASL--(Non-)Asbestos sheet Process Line		

All data quoted are based on our extensive tests and years of experience, however, they can only serve as guide values. Failure to select proper sealing products could result in property damage and/or serious injury. Specifications are subject to change without notice.

CAZ and aiflonseal are registered brands of CAZ Group Corporation