






# Raw Materials for Packing

## *Packing Materials*

Style	Specification	Description
	2g/m 3g/m 5g/m	For braided packing CAZ 250.  Pure PTFE yarn without oil, Grade A,B,C can satisfy different demands.  Normal Grade B & C is for core yarn.
<b>Y250—Pure PTFE Yarn (Without oil)</b>		
	2g/m 3g/m 5g/m	编织 CAZ 250L 盘根。  无油四氟线 A、B、C 等级能满足不同的需求， 一般 B、C 级作芯子线。
<b>Y250L—Pure PTFE Yarn with oil</b>		
	6000D, 0.7g/m 12000D, 1.4g/m 24000D, 2.7g/m	For braided packing CAZ 252.  Multiple PTFE filament yarn.  Y252P---impregnated with PTFE.
<b>Y252—Multiple PTFE filament yarn (impregnated with PTFE)</b>		
	2g/m 3g/m 5g/m	For braided packing CAZ 254.  Graphited PTFE yarn without oil. Grade A,B,C can satisfy different demands. Normal Grade B & C is for core yarn.  Y254L is graphited PTFE with oil.
<b>Y254—Graphited PTFE yarn</b>		
	2g/m 3g/m 5g/m	For braided packing CAZ 254CGFO.  Graphited PTFE with graphite sandwich,  Chinese “GFO”
<b>Y254GFO—Chinese “GFO”</b>		

## Raw Materials for Packing

## *Packing Materials*

Style	Specification	Description
	2g/m 3g/m 5g/m 10g/m	For braided packing CAZ 240. Made of flexible graphite reinforced with cotton, glass fiber, polyester fiber, carbon fiber etc. <b>Y240E</b> -graphite yarn with Inconel wire Other reinforcement materials: SS304, Copper, Nickel etc <b>Y240P</b> -graphite yarn impregnated with PTFE
<b>Y240--Expanded Graphite Yarn</b>		
	2g/m 3g/m 5g/m 10g/m	For braided packing CAZ 240M.  Inconel wire reinforced graphite yarn, jacketed with inconel mesh, <b>Y240AM</b> Graphite yarn jacketed with Aramid mesh
<b>Y240M--Inconel Reinforced Graphite yarn external braided with Inconel mesh</b>		
	6K 12K	For braided packing CAZ 242.  Carbonized fiber yarn, belongs to intermediate phase between PAN and carbon fiber  <b>Y242P</b> , PTFE impregnated is also available
<b>Y242--Carbonized fiber Yarn</b>		
	EK300-3p	Spun carbonized fiber yarn Normal reinforced with glassfiber in core  PTFE impregnated is also available
<b>Y242S--Spun Carbonized fiber yarn</b>		
	3k 6k 12k 24k	For braided packing CAZ 244.  Carbon fiber yarn, Made in Japan or TaiWan.  Graphite and lubricant impregnated is also available
<b>Y244—Carbon fiber yarn</b>		

## Raw Materials for Packing

## *Packing Materials*

Style	Specification	Description
	Type 989 DTX 6300 DEN 5680	For braided packing CAZ 260. Kevlar / Aramid yarn from Dupont. PTFE and Silicone oil impregnated is also available
<b>Y260--Kevlar Yarn</b>		
	EK300-3p	Spun Kevlar /Aramid yarn, Normal reinforced with glassfiber in core. PTFE and Silicone oil impregnated is also available
<b>Y262--Spun Kevlar yarn</b>		
	EK300-2p	For braided packing CAZ 264. Spun Nomex yarn reinforced with glassfiber in core. PTFE and Silicone oil impregnated is also available.
<b>Y264S--Spun Nomex yarn</b>		
	EK300-2P	For braided packing CAZ 220 & 220G. Glass fiber reinforced on request. PTFE and Silicone oil impregnated is also available
<b>Y220—Ramie yarn</b>		
	EK300-3P	For braided packing CAZ 230 & 230G. Normal reinforced with glassfiber core. PTFE and Silicone oil impregnated is also available.
<b>Y230—Arcylic fiber yarn</b>		

All data quoted are based on our extensive tests and years of experience, however, they can only serve as guide values. Failure to select proper sealing products could result in property damage and/or serious injury. Specifications are subject to change without notice.

**CAZ and aiflonseal are registered brands of CAZ Group Corporation**

# Raw Materials for Packing

## *Packing Materials*

Style	Specification	Description
	Dia. 2mm, 2P	For braided packing CAZ 234. 100% Kynol yarn (Novoloid). PTFE and Silicone oil impregnated is also available.
<b>Y234—Kynol fiber Yarn</b>		
	EK300-3P	Spun Kynol yarn (Novoloid) with fiberglass core. PTFE and Silicone oil impregnated is also available.
<b>Y234S—Spun Kynol fiber Yarn</b>		
	<p><b>Ceramic yarn:</b> 500~2000tex -1~2P; 525tex,630tex,700tex, 830tex,1000tex</p> <p><b>Dust free asbestos yarn:</b> Dia. 2mm,3mm,5mm</p> <p><b>Asbestos yarn (dusted):</b> 500~3000tex-1~3p</p>	<p>More fiberglass, ceramic fiber and asbestos yarn, please contact CAZtex, see to: <a href="http://www.caztex.net">www.caztex.net</a></p> <p><b>Glassfiber yarn:</b> Twisted yarn-12~800tex; Roving yarn-200~2400tex; Texturized yarn200~2400tex;</p>
<b>More CAZ Fiberglass, Ceramic and Asbestos yarn</b>		
	Dia. 3mm~14mm	Red silicon rubber cord with good elasticity, is for core of braided packing.
<b>CO460SC-Red Silicon rubber cord</b>		
	<p>PTFE Emulsion: 25kgs/barrel</p> <p>Graphite Emulsion: 50kgs/barrel</p>	PTFE Emulsion and is for dipping fiber packing, for example, graphite, Keval, Ramie, Arcylic, Novoloid, Carbon, Asbestos etc.
<b>PTFE-EM &amp; Graph-EM</b>		

All data quoted are based on our extensive tests and years of experience, however, they can only serve as guide values. Failure to select proper sealing products could result in property damage and/or serious injury. Specifications are subject to change without notice.

**CAZ and aiflonseal are registered brands of CAZ Group Corporation**