

*Non-asbestos Sheet*  
**CAZ-NCAF 432,433,434**

*Joint Sheets*

**CONSTRUCTION:**

CAZ NCAF Non-asbestos sheet is made from synthetic fibre, natural rubber, filling material and dye, compressed and calendered under high temperature and pressure into a sheet form. It eliminates asbestos-rubber sheet essentially and thoroughly.

**PARAMETER:**

Item	Style		
	432	433	434
Density g/cm <sup>3</sup>	1.8~2.0	1.8~2.0	1.8~2.0
Tensile strength ≥Mpa	6	9	12.5
Compressibility ≥%	12±5	12±5	12±5
Recovery ≥%	40	45	45
Aging coefficient	0.9	0.9	0.9
Stress relaxation ≤%	45	45	45
Steam Sealing	Tmax: 200℃ Pmax: 2~3Mpa 30min no shock	Tmax: 300℃ Pmax: 4~5Mpa 30min no shock	Tmax: 400℃ Pmax: 8~9Mpa 30min no shock
Tmax: °C	200	300	400
Pmax: Mpa	1.5	3.0	5.0
Resistance to media	Water, seawater, steam, fuel, gases, salt solutions and many other media.		

Normal colour: Black with some white, Blue or Green-white etc.  
Available with tin steel, copper, SS304 etc. wire mesh insertion (**43\*M**)  
Also available with anti-stick (**43\*S**) or graphite coating (**43\*G**)  
With your logo on request.

**DIMENSIONS:**

**Sheets:**

Thickness: 0.4~5mm  
2000×1500mm; 1500×4000mm; 1500×1500mm; 1350×1500mm  
1500×1000mm; 1270×1270mm; 3810×1270mm

**Cut gaskets:**

G432, G433, G434

Dimensions according to drawings or and standards

