

Asbestos Beater Sheet
CAZ-ASB 400, 400V

Joint Sheets

CONSTRUCTION:

CAZ 400 Asbestos emulsion sheet

It is made from synthetic emulsion, asbestos fiber and filling material. Normal used for automobile, agricultural machinery, motorcycle, engineering machinery etc., suitable for lubricating oil under temperature 200°C

CAZ 400V Vulcanized Asbestos beat sheet

It has smooth face and high density compared with Style 400

APPLICATION & PARAMETER:

Gasket materials for explosion engine cylinder gaskets and chemical gaskets

Suitable to sealing lubricating oil at highest temperature 200°C

400 Asb strip is normal for filler of spiral wound gasket.

Item		Style	
		400	400V
Density	g/cm ³	0.9~1.1	1.2~1.4
Tensile strength	≥Mpa	2.5	5
Compressibility	≥%	40±7	20±5
Recovery	≥%	20	40
Stress relaxation	≤%	30	30
In 20# aviation oil, 150°C, 30min	Oil absorption	≤50%	≤30%
	Thick. increase	≤6%	≤12%
In water 15~30°C, 5h	Thick. increase	≤6%	≤12%

Normal color: Grey, Black, White, other color on request

Also available with anti-stick : **400S, 400VS**
or graphite coating : **400G, 400VG**

TOLERANCE:

Item	Tolerance	In same sheet
Thickness	±mm	mm
0.5	0.05	0.06
0.6-0.8	0.06	0.08
1-2	0.08	0.08

DIMENSIONS:

Sheets:

Width: 500mm; 1000mm
Length: 500mm; 1000mm; 1200; 1500mm
Thickness: 0.3~2.0mm

Cut gaskets:

G400, G400V

Dimension according to drawings or specifications and standards.

