

Asbestos Rubber Sheet
CAZ-CAF 412,413,414

Joint Sheets

CONSTRUCTION:

CAZ CAF are made from selected asbestos fibre, natural rubber, filling material and dye. A price worthy quality of dependable performance, plus adaptability to many sealing requirements makes this jointing the most economical sheet packing choice in the wide range of industrial fields.

PARAMETER:

Item	Style			
	412	413	414	414-2
Tensile strength≥Mpa	9	12	15	19
Aging coefficient	0.9	0.9	0.9	0.9
Loss on ignition ≤%	30	30	28	28
Compressibility ≥%	12±5	12±5	12±5	12±5
Recovery ≥%	40	40	45	45
Density g/cm ³	1.6~2.0			
Tmax: °C	200	300	400	450
Pmax: Mpa	2.3	3.5	5.0	6.0
Resistance to media	Water, seawater, steam, diluted acid & alkali, gases, alcohols, salt solutions etc. under temperature and pressure.			

Lower Grade on request
 Available color: Purple, red, black, grey etc.
 Available with tin steel, copper, SS304 etc. wire mesh insertion (**41*M**)
 Also available with anti-stick (**41*S**) or graphite coating (**41*G**)
 With your logo on request

DIMENSION:

Sheets:

4000×1500mm; 2000×1500mm; 1500×1500mm;
 1500×1000mm; 1270×1270mm; 3810×1270mm;
 3810×2700mm
 Thickness: 0.5~6mm

Cut gaskets

G412~G414

Dimension according to drawings or and standards

