

Oil-resisting Asbestos Rubber Sheet
CAZ 412RO,413RO,414RO,415RO

Joint Sheets

CONSTRUCTION:

CAZ oil-resisting OCAF, a cost effective oil resistance asbestos-rubber sheets, are made from selected asbestos fiber, synthetic rubber, filling material and dye. Used in pipelines and apparatus of petrochemical & oil fields



PARAMETER:

| Item | Style | | | | |
|---------------------------------------|------------------------------------|-------|-------|-------|------|
| | 412RO | 413RO | 414RO | 415RO | |
| Tensile strength≥Mpa | 9 | 11 | 12.7 | 13 | |
| Compressibility≥% | 12±5 | | | | |
| Recovery≥% | 35 | 45 | 50 | 50 | |
| Density g/cm ³ | 1.6~2.0 | | | | |
| Tmax: °C | 200 | 300 | 400 | 500 | |
| Pmax: Mpa | 1.5 | 2.5 | 3.0 | 4.0 | |
| At 20# air lub oil, 15~30°C for 30min | Tensile strength≥Mpa | 8 | 9 | 10.8 | 26 |
| | Oil absorption≤ % | 23 | 23 | 23 | 9 |
| | Thickness increase% | | 20 | 15 | 15 |
| At 75# gasoline /3# 15~30°C for 5h | Tensile strength≥Mpa | 6 | 7 | 7.9 | 14.7 |
| | Oil absorption≤ % | 22 | 22 | 22 | 15 |
| | Thickness increase% | | 25 | 25 | 20 |
| | Oil sealing Mpa | 8 | 10 | 12 | 14 |
| Resistance to media | Oils, refrigerators, solvents etc. | | | | |

Available colour: Green, blue, white etc.

Available with tin steel, SS304 etc. wire mesh insertion (**Style: 41*ROM**)

Also available with anti-stick (**Style:41*ROS**) or graphite coating (**Style: 41*ROG**)

With your logo on request

DIMENSION:

Sheets:

1500×4000mm, 1500×2000mm

1500×1350mm, 1500×1000mm

1270×3810mm, 1270×1270mm

New: 3810×2700mm

Thickness: 0.4~6mm

Cut gaskets

G412RO,G413RO,G414RO,G415RO

Dimension according to drawings or and standards.

