

*Arcylic Fiber Packing*  
CAZ- 230P,230R 230G

*Compression Packing*

**CONSTRUCTION:**



**CAZ 230P Arcylic Fiber Packing with PTFE**

Braided from high strength arcylic synthetic fiber pre-impregnated with PTFE, and re-impregnated during square braiding. It has excellent properties of sealing, lubricating and resistance to chemicals. **230L** is arcylic fiber packing with oil and few PTFE



**CAZ 230R Arcylic Fiber Packing with Rubber Core**

High elastic red silicone rubber core can absorb vibration, to control leakage, suitable for worn-out pumps.

**CAZ 230G Arcylic Fiber Packing Treated with Graphite**

Braided of high strength Arcylic synthetic fiber, treated with graphite and special lubrication. Much of graphite filler increases the service temperature and the density of the packing.

**APPLICATION:**

<b>230 230L 230R</b>	Excellent multi-service for a wide variety of uses throughout a plant. Used in pumps and valves, and can handle most chemicals except strong acid, strong alkali and strong oxidizer. Especially for the condition of middle temp. high-pressure, high-speed, and where contamination is not permitted.
<b>230G</b>	Universal packing for pumps and valves, and handle water, air, steam, mild acids and alkalis, all kinds of organic solvents and Chemicals. Especially suitable for the condition of high-temperature, high-pressure, medium speed.

**PARAMETER:**

	230, 230L	230G
T	260°C	350°C
PH	1~13	1~13
V	20m/s	15m/s
Rotating	20bar	25bar
Reciprocating	80bar	100bar
Valve	100bar	150bar
D(g/cm <sup>3</sup> )	1.1~1.3	1.1~1.3



**PACKAGING:**

in coils of 5 or 10 kg, other package on request.  
as prepressed rings----**R230, R230R, R230G**  
as precut length



**DIMENSIONS:**

Size mm	5	6	8	10	12	13	14	15	16	18	20	22	25
appr. m/kg	33	23	13	8.0	5.5	5.0	4.2	3.7	3.2	2.5	2.1	1.7	1.3
Appr. ft/lb	49	34	19	12	8.2	7.4	6.2	5.5	4.8	3.7	3.1	2.5	1.9
kg/coil	5 or 10												