

Other Process Lines

Sealing Machines

Style	Specification	Application
	<ol style="list-style-type: none"> Power:380AV, 50HZ, 5 KW; Working space: 4×6m; Max. Output: 500kg/day 	<p>For making expanded graphite ("worm")</p> <p>Raw materials: Acid graphite-5099 Heated by LPG or oil</p>
880 GEL--Graphite Expanding Line		
	<ol style="list-style-type: none"> Power:380AV, 50HZ, 15 KW; Working space: 4×15m; Max. Output: 300kg/day 	<p>Composite machine +Cutter, For making expanded graphite yarn, normal size: 2g/m, 3g/m, 5g/m; The reinforced material can be cotton, glassfiber etc</p>
880 GYL--Graphite Yarn Process Line		
	<ol style="list-style-type: none"> Power:380AV, 50HZ, 30 KW; Working space: 10×20m; Max. Output: 1000kg/day 	<p>For making expanded graphite roll With width 1000mm and thickness 0.2~1.2mm; 1500mm on request.</p>
880 GRL-- Graphite Roll Process Line		
	<ol style="list-style-type: none"> Power:380AV, 50HZ, 30 KW; Working space: 10×12m; Max. Output: 500kg/day 	<p>From dry asbestos fiber to wet asbestos yarn (Dust free), 2g/m, 3g/m, 5g/m etc.</p>
880 AYL--Asbestos Yarn (Dust Free) Process Line		
	<ol style="list-style-type: none"> Power:380AV, 50HZ, 30 KW; Working space: 20×30m; Max. Output: 1000kg/day Thickness: 0.4~6.0mm 	<p>For making asbestos-rubber sheet, oil-resisting asbestos-rubber sheet, and non asbestos sheet. Max. size: 4000×1500mm; 4500×1500mm; 3810×1270mm;</p>
880 ASL--(Non-)Asbestos sheet Process Line		